


XCT to YAMAHA G19 & G22 W/ GE CONTROLLERS

FOR SHUNT (SEPERATELY EXCITED) WOUND MOTORS

PART NO. DOC110-020



1	DIODE RATING	CONTRACTOR RATING
	1N4001 1N5408 MR754	DEM 200A 400A

2	CONTACTOR RATING	CONTRACTOR RATING
	DEM 200A 300A 400A	300A DR 400A 400A TD 500A

3	FUSE	CONTROLLER RATING
	ANN250 ANN400	400A DR LESS 450A DR MORE


4 PRE-CHARGE RESISTOR NOT NEEDED ON XCT UNITS

POWER WIRE RATING	CONTROLLER RATING
6AWG-4AWG	300A
4AWG-2AWG	400A
2AWG-1/0AWG	500A

J1	FUNCTION
1	RUN/TOW
2	FOOT SWITCH FORWARD
3	REVERSE
4	KEY SWITCH
5	THROTTLE VIPER
6	THROTTLE LOW
7	THROTTLE HIGH
8	HORN NEG
9	SOLENOID NEG
10	SOLENOID NEG
11	TACH OUT
12	TACH REF
13	TACH NEG
14	TACH NEG
15	NOT USED
16	NOT USED
17	NOT USED
18	NOT USED
19	NOT USED
20	NOT USED
21	NOT USED
22	NOT USED
23	NOT USED
B+	BATTERY POSITIVE
B-	BATTERY NEGATIVE
J9	MOTOR FIELD
J8	MOTOR FIELD
J7	MOTOR FIELD

NOTES:

- * FUSES REQUIRED FOR ALL INSTALLATIONS
- * DIODE REQUIRED ACROSS COILS / RELAYS
- * TOW/RUN SWITCH PREVENTS REGEN WHILE TOWING
- > ASSUMES FOOT SWITCH IS OPEN WHEN THROTTLE OFF
- > ALLTRAX RESERVES THE RIGHT TO CHANGE DOCUMENTATION WITHOUT NOTICE
- > ALLTRAX MAKES NO WARRANTY AS TO THE ACCURACY, SUFFICIENCY, OR SUITABILITY OF ANY TECHNICAL OR OTHER INFORMATION PROVIDED
- > SEE OPERATORS MANUAL FOR MORE INFORMATION



DO NOT SCALE DRAWING

REVISIONS		
REV.	ECO.	DATE
A	120814	021615
B	041315	041315
C	050215	050215

DWG SCALE:	NTS
DRAWN:	R CSUK
ENGR:	D.Crockett
DATE:	111014

PROPRIETARY
THIS TECHNICAL DATA IS PROPRIETARY AND ALL RIGHTS ARE RESERVED. REPRODUCTION OR DISSEMINATION WITHOUT PERMISSION OF ALLTRAX INC.

TITLE	XCT to YAMAHA G19/22
WRITING DIAGRAM	Wiring Diagram
SIZE	A
DOCUMENT NO.	S
DOC110-020	
REV.	C